
# NASA TECH BRIEF



NASA Tech Briefs are issued to summarize specific innovations derived from the U. S. space program and to encourage their commercial application. Copies are available to the public from the Clearinghouse for Federal Scientific and Technical Information, Springfield, Virginia 22151.

## Simple Device Facilitates Inert-Gas Welding of Tubes



#### The problem:

To provide a simple device that will maintain an argon, or other inert-gas, atmosphere over the weld areas on two tubes being joined along a line on their outer peripheries. Separate supply hoses which have been used to provide an argon atmosphere over both sides of a weld seam formed along contiguous tubes are awkward to handle.

#### The solution:

A metal Y-tube that simultaneously directs streams

of argon from a single supply hose over the weld areas on both sides of the workpieces.

## How it's done:

Three pieces of pliable metal tubing (e.g., 3/16-inch copper tubing) are soldered or brazed in a Y-configuration. The stem of the Y is inserted into the argon supply hose, and the other two branches are bent so that the outlet tips will be in contact with the junction of the tubes being welded. The device is advanced along the junction in step with the welding operation.

(continued overleaf)

This document was prepared under the sponsorship of the National Aeronautics and Space Administration. Neither the United States Government nor any person acting on behalf of the United States

Government assumes any liability resulting from the use of the information contained in this document, or warrants that such use will be free from privately owned rights.

## Note:

Inquiries concerning this innovation may be directed to:

Technology Utilization Officer Marshall Space Flight Center Huntsville, Alabama, 35812 Reference: B66-10155

## **Patent Status:**

No patent action is contemplated by NASA.

Source: W. B. Kelley and K. V. Carrithers of North American Aviation, Inc.
under contract to
Marshall Space Flight Center
(M-FS-558)